



PETRA POWER STEERING FLUID 4/64 OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/01/2013

Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
 Trade name : PETRA POWER STEERING FLUID 4/64 OZ
 Product code : PETRA7003B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : FOLLOW LABEL DIRECTIONS

1.3. Details of the supplier of the safety data sheet

Petra Oil Company
6100 West by Northwest Blvd. Ste. 190
77040 Houston, TX

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Acute Tox. 4 (Inhalation:dust,mist) H332
Eye Irrit. 2B H320

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H320 - Causes eye irritation
H332 - Harmful if inhaled

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash ... thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER/doctor/.../if you feel unwell
P337+P313 - If eye irritation persists: Get medical advice/attention

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification (GHS-US)
distillates (petroleum), hydrotreated heavy naphthenic	(CAS No) 64742-52-5	>= 85	Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2B, H320
2,6-di-tert-butylphenol	(CAS No) 128-39-2	0.054 - 0.2646	Not classified
Tail gas (petroleum), saturate gas plant mixed stream, C4-rich	(CAS No) 68478-32-0	0.054 - 0.2646	Not classified
dibutyl phosphonate	(CAS No) 1809-19-4	0.054 - 0.2646	Acute Tox. 4 (Dermal), H312
white mineral oil (petroleum)	(CAS No) 8042-47-5	0.03 - 0.06	Asp. Tox. 1, H304
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	(CAS No) 72623-86-0	0.03 - 0.06	Not classified
PARAFFINUM LIQUIDUM	(CAS No) 8012-95-1	0.03 - 0.06	Not classified

PETRA POWER STEERING FLUID 4/64 OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
toluene	(CAS No) 108-88-3	0.0054 - 0.0486	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Petroleum Naphtha	(CAS No) 64742-47-8	< 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Unsuitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

PETRA POWER STEERING FLUID 4/64 OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible products : Strong bases. strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

white mineral oil (petroleum) (8042-47-5)

USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
-----------	--------------------------------	---------------------

toluene (108-88-3)

USA ACGIH	ACGIH TWA (ppm)	20 ppm
-----------	-----------------	--------

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.
Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Respiratory protection : Wear approved mask.
Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : light yellow. amber.
Odor : characteristic.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
: 199 °C
Self ignition temperature : No data available
: No data available
Flammability (solid, gas) : No data available
Vapor pressure : > 1 mm Hg
Relative vapor density at 20 °C : No data available
Relative density : 0.9
Solubility : No data available
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

PETRA POWER STEERING FLUID 4/64 OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

white mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat; Experimental value,Rat; Experimental value)

2,6-di-tert-butylphenol (128-39-2)	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rat	> 1000 mg/kg (Rat)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit)

dibutyl phosphonate (1809-19-4)	
LD50 oral rat	3200 mg/kg (Rat)
LD50 dermal rabbit	1990 mg/kg (Rabbit)

toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg (5580 mg/kg bodyweight; Rat; Rat; Experimental value)
LD50 dermal rabbit	12223 mg/kg (>5000 mg/kg bodyweight; Rabbit; Rabbit; Experimental value; Other,>5000 mg/kg bodyweight; Rabbit; Rabbit; Experimental value; Other)
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classifiedBased on available data, the classification criteria are not met
Carcinogenicity : Not classified

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
IARC group	3

white mineral oil (petroleum) (8042-47-5)	
IARC group	3

toluene (108-88-3)	
IARC group	3

Reproductive toxicity : Not classifiedBased on available data, the classification criteria are not met
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classifiedBased on available data, the classification criteria are not met
Aspiration hazard : Not classifiedBased on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms : Harmful if inhaled.
Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.

SECTION 12: Ecological information

12.1. Toxicity

white mineral oil (petroleum) (8042-47-5)	
LC50 fish 1	> 100 mg/l (96 h; Oncorhynchus mykiss; NOMINAL CONCENTRATION)
Threshold limit algae 1	≥ 100,72 h; Pseudokirchneriella subcapitata; GROWTH RATE

2,6-di-tert-butylphenol (128-39-2)	
EC50 Daphnia 1	0.45 mg/l (48 h; Daphnia magna; Flow-through system)

PETRA POWER STEERING FLUID 4/64 OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

toluene (108-88-3)	
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; LOCOMOTOR EFFECT)
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; TOXICITY TEST)
Threshold limit algae 2	105 mg/l (192 h; Microcystis aeruginosa)

12.2. Persistence and degradability

PETRA POWER STEERING FLUID 4/64 OZ	
Persistence and degradability	Not established.

Petroleum Naphtha (64742-47-8)	
Persistence and degradability	Not established.

white mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Not established.

PARAFFINUM LIQUIDUM (8012-95-1)	
Persistence and degradability	Not established.

2,6-di-tert-butylphenol (128-39-2)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water.

Tail gas (petroleum), saturate gas plant mixed stream, C4-rich (68478-32-0)	
Persistence and degradability	Not established.

dibutyl phosphonate (1809-19-4)	
Persistence and degradability	Biodegradability in water: no data available. Photodegradation in the air.

toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Not readily biodegradable in water. Biodegradable in the soil. Low potential for absorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	69 % ThOD

12.3. Bioaccumulative potential

PETRA POWER STEERING FLUID 4/64 OZ	
Bioaccumulative potential	Not established.

Petroleum Naphtha (64742-47-8)	
Bioaccumulative potential	Not established.

white mineral oil (petroleum) (8042-47-5)	
Bioaccumulative potential	No bioaccumulation data available.

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Bioaccumulative potential	Not established.

PARAFFINUM LIQUIDUM (8012-95-1)	
Bioaccumulative potential	Not established.

2,6-di-tert-butylphenol (128-39-2)	
BCF fish 1	660 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	800 (24 h; Chlorella sp.)
Log Pow	4.92
Bioaccumulative potential	Not established.

Tail gas (petroleum), saturate gas plant mixed stream, C4-rich (68478-32-0)	
Bioaccumulative potential	Not established.

dibutyl phosphonate (1809-19-4)	
Log Pow	1.81 (Estimated value)
Bioaccumulative potential	Bioaccumable.

PETRA POWER STEERING FLUID 4/64 OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

toluene (108-88-3)	
BCF fish 1	13.2 (Anguilla japonica)
BCF fish 2	90 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; FRESH WEIGHT)
BCF other aquatic organisms 2	4.2 (Mytilus edulis; FRESH WEIGHT)
Log Pow	2.73 (Experimental value; Other; 20 °C, Experimental value; Other; 20 °C, Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / ADN / IMDG / ICAO / IATA

US DOT (ground): NOT REGULATED,
ICAO/IATA (air): NOT REGULATED,
IMO/IMDG (water): NOT REGULATED,

14.2. UN proper shipping name

DOT Proper Shipping Name : NOT REGULATED

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

PETRA POWER STEERING FLUID 4/64 OZ	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard
distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
Petroleum Naphtha (64742-47-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

PETRA POWER STEERING FLUID 4/64 OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

Petroleum Naphtha (64742-47-8)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.


Full text of H-phrases: see section 16:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012) - Technical Chemical

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product