



Safety Data Sheet

Quick Glass Coating

9D05

SECTION 1: Identification of the substance

Product Name: Quick Glass Coating
Product Use: Automotive reconditioning product
Restrictions on Use: For automotive use only
Manufactured for: Petra Oil Company
11085 Regency Green Drive Cypress, TX 77429

Phone Number: (713) 856-5700
Fax Number: (713) 856-5712

Emergency Phone: CHEMTREC
1-800-424-9300
For International Calls: (703) 527-3887

SECTION 2: Hazards identification

Classification of the substance or mixture GHS-US classification
Label elements GHS-US labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US): WARNING

Hazard Statements (GHS-US):

H315 – Causes skin irritation
H320 – Causes eye irritation
H332 – Harmful if inhaled
H336 – May cause drowsiness or dizziness
H373 – May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US):

P210 – Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking.
P261 – Avoid breathing dust/fumes/gas/mist/vapors/spray
P262 – Do not get in eyes, on skin, or on clothing
P264 – Wash thoroughly after handling
P273 – Avoid release to the environment without proper governmental permits
P280 – Wear protective gloves/protective clothing/eye protection/face protection
P284 – In case of inadequate ventilation, wear respiratory protection
P301+P310 – IF SWALLOWED: immediately call POISON CENTER/doctor
P305+P351+P338 – IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P337+P313 – if eye irritation persists, get medical advice/attention
P303+P361+P353 – IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing
P402 – Store in a dry place
P402+P404 – Store in a dry place. Store in a closed container.

Other hazards

No additional information available

Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

Substances

Name	Product Identifier	%	GHS-US classification
Resin	Trade Secret	<50	Not established
silica	7631-86-9	<50	Not established
water	7732-18-5	>50	NA

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation: Remove to fresh air. Administer oxygen if there is difficulty in breathing. Obtain medical attention immediately, if necessary

First-aid measures after skin contact: Remove contaminated clothing without delay. Flush skin thoroughly with water. Do not reuse clothing without laundering.

First-aid measures after eye contact: Immediately irrigate with plenty of water for 15 minutes including under the eyelids. Obtain medical attention if irritation persists.

First-aid measures after ingestion: Call a physician immediately. ONLY induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact: May cause irritation, drying, redness, burning, and cracking

Symptoms/injuries after inhalation: May cause headache, dizziness, nausea

Symptoms/injuries after eye contact: Causes serious eye irritation and conjunctivitis

Symptoms/injuries after ingestion: May cause dizziness, nausea, headache, weakness, drowsiness, vomiting, and irritation of the digestive tract, loss of coordination, fatigue, muscle twitches, diarrhea, gastrointestinal irritation, unconsciousness, convulsions, and death.

Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or SDS at hand

SECTION 5: Firefighting measures

Suitable extinguishing media: Foam, alcohol foam, CO2, dry chemical

Reactivity: Strong oxidizing agents

Special Hazards Arising from Chemical: In event of fire, fire created carbon oxides may be formed.

Special Protective Actions for Firefighters: Wear positive pressure self-contained breathing apparatus; Wear full protective clothing.

This product is non-flammable. See Section 9 for Physical Properties.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures: Remove sources of ignition. Warn other works of spill. Wear protective equipment (NIOSH approved respirator, gloves, and safety glasses). Handle in accordance with good industrial hygiene and safety practice. For non-emergency personnel

Protective equipment: NIOSH approved respirator, gloves, and safety goggles

Emergency procedures: Evacuate unnecessary personnel.

For emergency responders

Protective equipment: Equip cleanup crew with NIOSH approved respirators, chemical resistant outerwear, gloves, and safety goggles.

Emergency procedures: Ventilate area.

Environmental precautions

Prevent entry to sewers and public waters. Do not allow material to be released into the environment without proper government permits.

Methods and material for containment and cleaning up

For containment: Absorb and/or contain spill with inert material, then place in suitable container.

Methods for cleaning up: Clear up spills immediately and dispose of waste safely.

Reference to other sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling: Do not breathe vapors or mists from spraying. Avoid contact with skin and eyes. Use with adequate ventilation to maintain exposure levels below established exposure limits. If required, wear an appropriate NIOSH approved respirator with paint filter.

Hygiene measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, dry place. Keep container tightly closed.

Incompatible products: Strong oxidizers.

Incompatible materials: Heat sources.

Storage area: Cool, dry, and away from heat sources

Special rules on packaging: Store only in original HDPE plastic container

Specific end use(s): Vehicle exterior cleaner and sealant

SECTION 8: Exposure controls/personal protection

Exposure controls

Engineering Controls: Exhaust ventilation, showers, eyewash stations, use in well ventilated area

Personal Protective Equipment: Safety goggles and nitrile gloves



Respiratory Protection: NA

Protective Gloves: Nitrile examination type

Eye Protection: Safety glasses with side shields or goggles

Ventilation: Local exhaust used to maintain below TWA limits

Mechanical: Use non-sparking equipment

Work/Hygienic Practices: Wash thoroughly after handling product and before eating, drinking, or smoking

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical State: Liquid, emulsion

Appearance: Milky white

Color: White

Odor: Slight solvent

Boiling Point: >200°F

Flash Point: >200°F

Specific Gravity: 1.0

Density: 8.33 lbs/gallon

Viscosity: N/A

SECTION 10: Stability and reactivity

Stability: Stable

Conditions to Avoid: Keep away from open flames, hot surfaces, sources of ignition, moist air, water

Incompatible Materials: Strong oxidizing agents. Material may react with water and certain protic solvents

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, hydrogen fluoride, hydrogen chloride gas

Hazardous Polymerization: None

SECTION 11: Toxicological information

Toxicological Information – Resin Polymer

Carcinogenicity information: Not listed as a carcinogen by NTP (National Toxicology Program); not regulated as a carcinogen by OSHA (Occupational Safety and Health Administration), not evaluated by IARC (International Agency for Research on Cancer)

Reported human effects: No human studies have been conducted on this material. The use of recommended protective equipment should prevent any adverse effects. No reports of adverse effects from workers handling this material have been received.

Reported animal effects: Oral LD50 rat: 200 – 2000 mg/kg. Skin irritation, rabbit: severe erythema with signs of necrosis after 1-hour exposure.

Toxicological Information – Hydrocarbon Solvent

Acute exposure effects

Skin contact: may cause irritation, drying, redness, burning, and cracking

Eye contact: may cause irritation and conjunctivitis

Ingestion: harmful or fatal if swallowed. May cause dizziness, nausea, headache, weakness, drowsiness, vomiting, irritation of digestive tract, loss of coordination, fatigue, muscle twitches, diarrhea, gastrointestinal irritation, unconsciousness, convulsions, and death.

Chronic exposure effects: Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage such as anemia, skin irritation, bone marrow, liver damage and jaundice. In addition, various organic solvents have exhibited mutagenic and teratogenic properties. For specific information regarding these effects, please see individual manufacturing data sheets for solvent components listed in Section 2.

SECTION 12: Ecological information

General comments: Do not allow material to be released into the environment without proper governmental permits.

SECTION 13: Disposal considerations

Waste Disposal Method:

Disposal should be made in accordance with federal, state and local regulations. Recovered non-usable material is a RCRA hazardous waste. Treatment, storage, transportation and disposal must be in accordance with EPA and State regulation under the authority of the Resource Conservation and Recovery Act (RCRA) 40 CFR parts 260-271

A competent and properly permitted contractor should do appropriate disposal. Incineration of combustible waste material in a permitted facility in accordance with the local, state, and federal regulations is the recommended disposal method.

SECTION 14: Transport information

Hazardous for shipping via ground: No. Via Air: No.

DOT Shipping Name: NA

DOT Hazard Class: NA

DOT Labels: NA

UN Number: NA

Packing Group: NA

Air (IATA): NA

SECTION 15: Regulatory information

SARA 313: This product does not contain any chemicals subject to reporting under Section 313 of the Title III of the Superfund Amendments and Reauthorization Act and 40CFR372.

CERCLA: This product does not contain any chemicals subject to reporting as a CERCLA Hazardous Substance under 40CFR302.4.

TSCA: The ingredients in this product are TSCA listed and EPA compliant.

EU Labeling:

Xn: Harmful

EU Risks and Safety Phrases:

R22: Harmful if swallowed

R34: Causes severe skin burns

S16: Keep away from sources of ignition. No smoking

S23: Do not breathe gas/fumes/vapor/spray

S24/25/26: Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S28: After contact with skin, wash immediately with plenty of water

S37/39: Wear suitable gloves and eye/face protection

SECTION 16: Other information

Prepared by: Feynlab, LLC.

Revision Date: 3/23/2016

Revision Summary: This document has been updated to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Feynlab's knowledge or obtained from sources believed by Feynlab to be accurate. Feynlab does not assume any legal responsibility for use or reliance upon same. Before using any chemical, read its label, instructions and safety data sheet.